

TIPO	TYPE	G 2										TYPE	TYPE				
		100	160	200	250	315	400	500	630	800	1000			ALSO TWO PISTONS	AUSSI À DEUX PISTONS		
FORZA MAX. DI LAVORO	KN	STOESSELKRAFT	KN	100÷1000	160÷1600	200÷2000	250÷2500	315÷3150	400÷4000	500÷5000	630÷6300	800÷8000	1000÷10000	MAX FORCE OF RAM	KN	FORCE DU TRAVAIL	KN
FORZA DI RITORNO	KN	RUECKZUGKRAFT	KN	100	160	160	200	250	350	400	600	750	800	RETURN CAPACITY	KN	FORCE AU RETOUR	KN
CORSA SLITTA	mm	STOESSELHUB	mm	600	800	800	800	800	1000	1000	1200	1200	1200	STROKE OF RAM	mm	COURSE COULISSEAU	mm
LUCE TRA I MONTANTI	mm	SEITLICHESTAENDE-ROEFFNUNG	mm	920	1120	1120	1220	1420	1620	1820	2020	2520	2520	SPACE BETWEEN UPRIGHTS	mm	LARGEUR UTILE	mm
LUCE TRA TAVOLA E SLITTA	mm	EINBAUHOEHE	mm	800	1000	1000	1200	1200	1300	1400	1500	1800	1800	RAM HEIGHT	mm	HAUTEUR OUTIL FERME	mm
DIMENSIONI TAVOLA	mm	TISCHFLAECHE	mm	900 x 900	1100x900	1100x900	1200x1000	1400x1200	1600x1200	1800x1400	2000x1400	2500x1600	2500x1600	TABLE AREA	mm	SURFACE TABLE	mm
DIMENSIONI SLITTA	mm	STOESSELFLAECHE	mm	900 x 900	1100x900	1100x900	1200x1000	1400x1200	1600x1200	1800x1400	2000x1400	2500x1600	2500x1600	RAM AREA	mm	SURFACE COULISSEAU	mm
VELOCITÀ DI AVVICINAMENTO SLITTA	mm/sec	STOESSELGE-SCHW. AB	mm/sec	A 400 B 500 C 500 D 660	400 500 500 660	400 500 500 660	400 500 500 660	400 500 500 660	400 500 500 660	400 400 500 500	400 400 500 500	400 400 500 500	400 400 500 500	RAPID CLOSING SPEED	mm/sec	VITESSE DE FERMETURE	mm/sec
VELOCITÀ DI LAVORO SLITTA	mm/sec	STOESSELGE-SCHW. LAST	mm/sec	A 22 B 22 ÷ 35 C 28 ÷ 55 D 36 ÷ 62	18 18 ÷ 40 23 ÷ 46 28 ÷ 65	18 18 ÷ 32 23 ÷ 50 28 ÷ 74	18 18 ÷ 25 23 ÷ 50 28 ÷ 65	15 15 ÷ 25 23 ÷ 50 30 ÷ 65	15 18 ÷ 25 28 ÷ 38 38 ÷ 48	15 15 ÷ 30 23 ÷ 38 30 ÷ 60	15 15 ÷ 25 23 ÷ 32 30 ÷ 50	15 14 ÷ 24 18 ÷ 37 20 ÷ 47	15 15 ÷ 30 23 ÷ 38 25 ÷ 45	WORK SPEED	mm/sec	VITESSE DE TRAVAIL	mm/sec
VELOCITÀ DI RITORNO SLITTA	mm/sec	STOESSELGE-SCHW. AUF	mm/sec	A 220 B 360 C 560 D 640	180 390 440 640	240 400 500 660	230 320 500 660	200 390 500 660	200 380 500 660	200 380 500 660	170 280 360 500	150 260 400 500	200 380 400 500	RAPID RETURN SPEED	mm/sec	VITESSE DE RETOUR	mm/sec
FORZA CUSCINO INFERIORE	KN	ZIEHKISSENKRAFT	KN	50 ÷ 500	80 ÷ 800	100÷1000	125 ÷ 1250	160÷1600	200 ÷ 2000	250 ÷ 2500	315 ÷ 3150	400 ÷ 4000	500 ÷ 5000	MAX. FORCE CUSHION	KN	FORCE COUSSIN	KN
CORSA CUSCINO INFERIORE	mm	ZIEHKISSENHUB	mm	300	300	300	300	300	400	400	400	500	500	STROKE CUSHION	mm	COURSE COUSSIN	mm
DIMENSIONI CUSCINO INFERIORE	mm	ZIEHKISSEN-FLAECHE	mm	700x700	900 x 700	900 x 700	1000 x 800	1200 x 1000	1400 x 1000	1600 x 1200	1800 x 1200	2200 x 1300	2200x1300	AREA CUSHION	mm	SURFACE COUSSIN	mm
POTENZA ELETTRICA INSTALLATA	KW	ANTRIEBSLEISTUNG	KW	A 22 B 22 C 30 D 37	30 30 37 44	37 37 44 55	44 44 55 74	44 44 74 92	55 74 110 147	74 74 110 147	92 92 147 184	110 110 147 220	147 147 220 330	INSTALLED POWER	KW	PUISSANCE MOTEUR	KW
DIMENSIONI INGOMBRO	mm	PRESSENMASSE	mm	1800x1600 H 4000	2100x1700 H 4800	2100x1700 H 5000	2200x1900 H 5200	2400x2100 H 5400	2600x2400 H 5800	2800x2400 H 6600	3000x2500 H 6800	3800x2800 H 8600	3800x3000 H 8800	SIZE OF MACHINE	mm	ENCOMBREMENT	mm
* FORZA ESTRATTORE	KN	AUSWERFERKRAFT	KN	50	100	150	200	300	300	400	500	600	700	FORCE EJECTOR	KN	FORCE EJECTEUR	KN
CORSA ESTRATTORE	mm	AUSWERFERHUB	mm	200	300	300	300	400	400	400	400	400	400	STROKE EJECTOR	mm	COURSE EJECTEUR	mm

* (OPTIONAL) ESTRATTORE IDRAULICO O TERZO EFFETTO SUPERIORE
* (OPTIONAL) AKTIV AUSWERFER

* (OPTIONAL) HYDRAULIC EJECTOR OR 3° UPPER EFFECT
* (OPTIONAL) EJECTEUR HYDRAULIQUES OU 3° EFFET SUPERIEUR